

Solo

Fan convectors

Incorporating intelligent technology, the new Solo fan convectors from Grant UK are small, quiet, efficient and effective.

The Solo convector range includes the wall-mounted Solo Compact and Solo CompactMAX and the space saving plinth heater, the Solo Hideaway. Each unit is highly efficient and ideally suited to complement low temperature systems including heat pumps such as the Grant Aeron3.



Integrates seamlessly with low temperature systems



No thermostatic radiator valves required



High efficiency



Adjustable temperature controls



Faster rate of convection



Low surface temperature



Small and slim in size



Individually controlled zones



5 year guarantee



www.grantuk.com



Technical Specifications

		Solo Compact	Solo CompactMAX	Solo Hideaway
Height	mm	410	410	120
Width	mm	610	985	700
Depth	mm	110	110	418
Weight	kg	8.2	13.8	6.6
Hydraulic connections	mm	15	15	15
Water content	Litre	0.15	0.3	0.15
Normal voltage	V	230	230	230
Fuse rating	A	3	3	3
PERFORMANCE (BS EN ISO 16430)				
Heating capacity at Mean Water Flow Temperature at high/low				
Temperature 35°C	W	314/247	604/470	314/247
Temperature 40°C	W	426/335	831/646	426/335
Temperature 45°C	W	542/426	1072/832	542/426
Temperature 50°C	W	660/519	1318/1024	660/519
Temperature 55°C	W	780/613	1571/1220	780/613
Temperature 60°C	W	901/708	1828/1420	901/708
Temperature 65°C	W	1023/803	2090/1623	1023/803
Temperature 70°C	W	1146/900	2356/1830	1146/900
SOUND PRESSURE LEVEL (ISO 3744)				
Low	dB(A) at 1 m	18	18	18
High	dB(A) at 1 m	22	23	22
Boost	dB(A) at 1 m	38	39	38
AIR FLOW RATE (ISO 5801)				
Low	m3/hr	35	70	35
High	m3/hr	60	120	60
Boost	m3/hr	115	230	115
POWER INPUT				
Low	W	8	13	8
High	W	10	19	10
Boost	W	20	36	20
Standby power	W	4	4	4